



# Insulation

## Fabufill CEILING INSULATION

### WHAT NATURE WOULD CHOOSE

- ✓ COST EFFECTIVE
- ✓ NON ALLERGENIC
- ✓ NON ITCH
- ✓ NON FLAMMABLE
- ✓ THERMAL
- ✓ 100% RECYCLABLE
- ✓ 100% ECO & NATURE FRIENDLY
- ✓ FIRE TESTED SANS 428 (B/B1/2)
- ✓ SABS APPROVED
- ✓ **B GRADE SPECIALS AVAILABLE**
- ✓ THICKNESS FROM 40 MM UP TO 100 MM



| Thickness (mm) | Dimensions (mm)   | R Value M <sup>2</sup> k/w |
|----------------|-------------------|----------------------------|
| 40mm           | 10000 x 1200 x 40 | 0.94                       |
| 50mm           | 10000 x 1200 x 50 | 1.15                       |
| 75 mm          | 8000 x 1200 x 75  | 1.69                       |
| 100 mm         | 6000 x 1200 x 100 | 2.20                       |

(SABS testing concluded and accredited)



# Polycarbonate

25 Years Limited warranty on all Suntuf Polycarbonate




### Profiles available:

#### IBR ( 1mm )

Colours: Blue, green, bronze, clear, opal, diffused, heatstop


#### IBR ( 1.25 mm )

Colours: Bronze, clear, opal, diffused, heatstop




#### Corrugated 10.5 RIB ( 1mm only)

Colours: Bronze, opal, clear



#### Widespan ( 1mm & 1.25mm )

Colours: Clear, opal, diffused, heatstop



#### Grecca ( 1mm only)

Colours: Bronze, opal, clear, green



- Rust Proof
- Hail Proof
- UV Protected on both sides
- Specialised fixings available
- 250 times stronger than glass
- Manufactured out of pure virgin resin.
- Virtually unbreakable.
- Polycarbonate flat sheet & multiwall products available.
- enquire within.

Terms & Conditions Apply

# Chromadek

Profiles available: IBR  
Corrugated  
Widespan

### ★ Minimum quantity orders

Accessories : Bullnosing  
Ridgings  
Flashings  
Cranking  
Standard undercoat colour - Pebble Grey



|                         |                         |                       |
|-------------------------|-------------------------|-----------------------|
|                         |                         |                       |
| Fish Eagle White N14128 | Azure Blue N 01109      | White Lion N 15010    |
|                         |                         |                       |
| Buffalo Brown N 09412   | Sandstone Beige N 15355 | Aloe Green N 03286    |
|                         |                         |                       |
| Gembok Sand N 15355     | Traffic Green N 03002   | Umhlanga Wave N 02103 |
|                         |                         |                       |
| Dove Grey N 13639       | Kingfisher Blue N 01029 | Dark Dolphin N 13030  |
|                         |                         |                       |
| Kalahari Red N 06551    | Charcoal Grey N 13012   |                       |

## Galvanised



Profiles available: IBR  
Widespan  
Corrugated 10.5 RIB  
Corrugated 8.5 RIB  
also available in  
0.25mm & 0.27mm.

### Available in the following thicknesses.

- 0.4 mm
- 0.5 mm
- 0.58 mm
- 0.8 mm

- Production lead-time of ± 6 - 9 working days, coil pending.
- Lengths from 1.8m up to 13 m.
- Customer responsible to offload vehicle on-site.

